Tennant 6200

The perfect combination of high efficiency and compact size. This small, manoeuvrable sweeper with a cleaning path of 107cm to 140cm is able to match the productivity and performance of much larger machines. The Tennant 6200 power sweeper is ideal for use in large congested buildings and in light outdoor applications. The machine's compact dimensions and accurate steering, allow it to clean in narrow aisles and turn in very tight spaces.



Features

- VCS™ filter shaking cleaning system
- High-dump hopper
- · Overthrow sweeping technology
- Vacuum wand
- · Perma filter
- Easy controls
- Corner rollers
- No-tool brush & dust filter change

Benefits

- Perfect dust control
- For automatic emptying into a container up to 135cm
- Ensures good performance even with worn brushes
- Extends cleaning reach & increases producitivity
- Extends dust filter life
- Ease of operation
- Helps to protect property and machine in tight corners
- Quick & easy maintenance

Applications

- · Warehouse & distribution facilities
- Manufacturing & production facilities
- · Shopping centres

- · Contract cleaning
- Transport & logistics sector



High-dump hopper



No-tool filter change



Overhead guard & vacuum wand



Machine in action



TECHNICAL SPECIFICATIONS 6200

		Е	LPG	Diesel
Machine Dimensions				
Working width (single side brush) Working width (dual side brushes) Dimensions (lxwxh) Machine weight (net)	cm cm cm kg	107 140 196x112x144 565	107 140 196x112x144 620	107 140 196x112x144 630
Sweeping System				
Area coverage theoretical (max) Area coverage practical (max) Length main brush x dia Diameter side brush Sweeping principle Transaxle drive	m²/h m²/h cm cm yes/no	13,580 8125 71 x 28 52 overthrow yes	11,200 8125 71 x 28 52 overthrow yes	11,200 8125 71 x 28 52 overthrow yes
Recovery System				
Panel filter capacity Airflow Hopper capacity, volume Hopper capacity, weight Hopper dump height	m² L/s L kg cm	4.6 118 125 135 135	4.6 118 125 135 135	4.6 118 125 135 135
Power				
Power source Total power consumption Protection class Sound level (DIN45635)	W 1/11/111 dB(A)	36V 2910 III 68	12V 8200 III 81	12V 10,400 III 83
Propelling				
Transport speed Working speed Climbing capacity Turning circle	km/h km/h % cm	9.7 6.5 18 210	8 6.5 18 210	8 6.5 18 210

Configuration

- Battery
- Diesel

The above mentioned configuration includes as standard a right hand side brush, 135cm multilevel dump, flashing light and back-up alarm.

Accessories


• Brushes • Batteries • Chargers

Options

• Front & rear lights • Left side brush • Vacuum wand (E) • Overhead guard

Warranty

24 Months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, whichever comes first, excluding wear items.



TENNANT NV

Industrielaan 6, 5405 AB Uden P.O. Box 6, 5400 AA Uden THE NETHERLANDS Tel: 00800-2255 8366 Fax: 00800-3298 3662 E-mail: europe@tennantco.com

www.tennant-europe.com

TENNANT UK LTD.

Gladstone Road Northhampton NN5 7RX UNITED KINGDOM Tel: 00800-2255 8366 Fax: 00800-3298 3662

Tel: 01604 583191 (local rate UK only) Fax: 01604 587909 (local rate UK only) E-mail: europe@tennantco.com

995470-06/05

